

TCK User's Guide for Technology Implementors

Table of Contents

Eclipse Foundation	1
Preface	2
Who Should Use This Book	2
Before You Read This Book	2
Typographic Conventions	2
Shell Prompts in Command Examples	3
1 Introduction	4
1.1 Compatibility Testing	4
1.2 About the TCK	6
1.3 Getting Started With the TCK	9
2 Procedure for Certification	10
2.1 Certification Overview	10
2.2 Compatibility Requirements	10
2.3 Test Appeals Process	15
2.4 Specifications for Jakarta Servlet	17
2.5 Libraries for Jakarta Servlet	17
3 Installation	18
3.1 Obtaining a Compatible Implementation	18
3.2 Installing the Software	18
4 Setup and Configuration	20
4.4 Custom Configuration Handlers	20
4.5 Custom Deployment Handlers	20
4.6 Using the JavaTest Harness Software	22
4.7 Using the JavaTest Harness Configuration GUI	22
5 Executing Tests	26
5.1 Starting JavaTest	26
5.2 Running a Subset of the Tests	27
5.3 Running the TCK Against another CI	29
5.4 Running the TCK Against a Vendor's Implementation	29
5.5 Test Reports	30
6 Debugging Test Problems	32
6.1 Overview	32
6.2 Test Tree	33
6.3 Folder Information	33
6.4 Test Information	33
6.5 Report Files	34

6.6 Configuration Failures	34
6.7 Troubleshooting Tips	34
A Frequently Asked Questions	36
A.1 Where do I start to debug a test failure?	36
A.2 How do I restart a crashed test run?	36
A.3 What would cause tests be added to the exclude list?	36
B Packaging the Test Applications in Servlet-Compliant WAR Files With VI-Specific Information	37
B.1 Overview	37
B.2 Creating the TCK VI-Specific Servlet-Compliant WAR Files	38

Eclipse Foundation

Technology Compatibility Kit User's Guide for Jakarta Servlet

Release 5.0 for Jakarta EE

September 2020

Technology Compatibility Kit User's Guide for Jakarta Servlet, Release 5.0 for Jakarta EE

Copyright © 2017, 2020 Oracle and/or its affiliates. All rights reserved.

This program and the accompanying materials are made available under the terms of the Eclipse Public License v. 2.0, which is available at <http://www.eclipse.org/legal/epl-2.0>.

SPDX-License-Identifier: EPL-2.0

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

References in this document to Java Servlet refer to the Jakarta Servlet unless otherwise noted.

Preface

This guide describes how to install, configure, and run the Technology Compatibility Kit (TCK) that is used to test the Jakarta Servlet (Servlet 5.0) technology.

The Servlet TCK is a portable, configurable automated test suite for verifying the compatibility of a vendor's implementation of the Servlet 5.0 Specification (hereafter referred to as the vendor implementation or VI). The Servlet TCK uses the JavaTest harness version 5.0 to run the test suite



Note All references to specific Web URLs are given for the sake of your convenience in locating the resources quickly. These references are always subject to changes that are in many cases beyond the control of the authors of this guide.

Jakarta EE is a community sponsored and community run program. Organizations contribute, along side individual contributors who use, evolve and assist others. Commercial support is not available through the Eclipse Foundation resources. Please refer to the Eclipse EE4J project site (<https://projects.eclipse.org/projects/ee4j>). There, you will find additional details as well as a list of all the associated sub-projects (Implementations and APIs), that make up Jakarta EE and define these specifications. If you have questions about this Specification you may send inquiries to servlet-dev@eclipse.org. If you have questions about this TCK, you may send inquiries to jakartaee-tck-dev@eclipse.org.

Who Should Use This Book

This guide is for vendors that implement the Servlet 5.0 technology to assist them in running the test suite that verifies compatibility of their implementation of the Servlet 5.0 Specification.

Before You Read This Book

You should be familiar with the Servlet 5.0, version 5.0 Specification, which can be found at <https://jakarta.ee/specifications/servlet/5.0/>.

Before running the tests in the Servlet TCK, you should familiarize yourself with the JavaTest documentation which can be accessed at the [JT Harness web site](#).

Typographic Conventions

The following table describes the typographic conventions that are used in this book.

Convention	Meaning	Example
Boldface	Boldface type indicates graphical user interface elements associated with an action, terms defined in text, or what you type, contrasted with onscreen computer output.	From the File menu, select Open Project . A cache is a copy that is stored locally. <code>machine_name% *su*</code> <code>Password:</code>
Monospace	Monospace type indicates the names of files and directories, commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name% you have mail.</code>
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.	Read Chapter 6 in the <i>User's Guide</i> . Do <i>not</i> save the file. The command to remove a file is <code>rm filename</code> .

Shell Prompts in Command Examples

The following table shows the default UNIX system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

Shell	Prompt
C shell	<code>machine_name%</code>
C shell for superuser	<code>machine_name#</code>
Bourne shell and Korn shell	<code>\$</code>
Bourne shell and Korn shell for superuser	<code>#</code>
Bash shell	<code>shell_name-shell_version\$</code>
Bash shell for superuser	<code>shell_name-shell_version#</code>

1 Introduction

This chapter provides an overview of the principles that apply generally to all Technology Compatibility Kits (TCKs) and describes the Jakarta Servlet TCK (Servlet 5.0 TCK). It also includes a high level listing of what is needed to get up and running with the Servlet TCK.

This chapter includes the following topics:

- [Compatibility Testing](#)
- [About the TCK](#)
- [Getting Started With the TCK](#)

1.1 Compatibility Testing

Compatibility testing differs from traditional product testing in a number of ways. The focus of compatibility testing is to test those features and areas of an implementation that are likely to differ across other implementations, such as those features that:

- Rely on hardware or operating system-specific behavior
- Are difficult to port
- Mask or abstract hardware or operating system behavior

Compatibility test development for a given feature relies on a complete specification and compatible implementation (CI) for that feature. Compatibility testing is not primarily concerned with robustness, performance, nor ease of use.

1.1.1 Why Compatibility Testing is Important

Jakarta platform compatibility is important to different groups involved with Jakarta technologies for different reasons:

- Compatibility testing ensures that the Jakarta platform does not become fragmented as it is ported to different operating systems and hardware environments.
- Compatibility testing benefits developers working in the Jakarta programming language, allowing them to write applications once and then to deploy them across heterogeneous computing environments without porting.
- Compatibility testing allows application users to obtain applications from disparate sources and deploy them with confidence.
- Conformance testing benefits Jakarta platform implementors by ensuring a level playing field for

all Jakarta platform ports.

1.1.2 TCK Compatibility Rules

Compatibility criteria for all technology implementations are embodied in the TCK Compatibility Rules that apply to a specified technology. Each TCK tests for adherence to these Rules as described in [Chapter 2, "Procedure for Certification."](#)

1.1.3 TCK Overview

A TCK is a set of tools and tests used to verify that a vendor's compatible implementation of a Jakarta EE technology conforms to the applicable specification. All tests in the TCK are based on the written specifications for the Jakarta EE platform. A TCK tests compatibility of a vendor's compatible implementation of the technology to the applicable specification of the technology. Compatibility testing is a means of ensuring correctness, completeness, and consistency across all implementations developed by technology licensees.

The set of tests included with each TCK is called the test suite. Most tests in a TCK's test suite are self-checking, but some tests may require tester interaction. Most tests return either a Pass or Fail status. For a given platform to be certified, all of the required tests must pass. The definition of required tests may change from platform to platform.

The definition of required tests will change over time. Before your final certification test pass, be sure to download the latest version of this TCK.

1.1.4 Jakarta EE Specification Process (JESP) Program and Compatibility Testing

The Jakarta EE Specification Process (JESP) program is the formalization of the open process that has been used since 2019 to develop and revise Jakarta EE technology specifications in cooperation with the international Jakarta EE community. The JESP program specifies that the following three major components must be included as deliverables in a final Jakarta EE technology release under the direction of the responsible Expert Group:

- Technology Specification
- Compatible Implementation (CI)
- Technology Compatibility Kit (TCK)

For further information about the JESP program, go to Jakarta EE Specification Process community page <https://jakarta.ee/specifications>.

1.2 About the TCK

The Servlet TCK 5.0 is designed as a portable, configurable, automated test suite for verifying the compatibility of a vendor's implementation of the Servlet 5.0 Specification.

1.2.1 TCK Specifications and Requirements

This section lists the applicable requirements and specifications.

- **Specification Requirements:** Software requirements for a Servlet implementation are described in detail in the Servlet 5.0 Specification. Links to the Servlet specification and other product information can be found at <https://jakarta.ee/specifications/servlet/5.0/>.
- **Servlet Version:** The Servlet 5.0 TCK is based on the Servlet Specification, Version 5.0.
- **Compatible Implementation:** One Servlet 5.0 Compatible Implementation, Eclipse GlassFish 6.0 is available from the Eclipse EE4J project (<https://projects.eclipse.org/projects/ee4j>). See the CI documentation page at <https://projects.eclipse.org/projects/ee4j.glassfish> for more information.

See the Servlet TCK Release Notes for more specific information about Java SE version requirements, supported platforms, restrictions, and so on.

1.2.2 TCK Components

The Servlet TCK 5.0 includes the following components:

- JavaTest harness version 5.0 and related documentation. See [JT Harness web site](#) for additional information.
- Servlet TCK signature tests; check that all public APIs are supported and/or defined as specified in the Servlet Version 5.0 implementation under test.
- If applicable, an exclude list, which provides a list of tests that your implementation is not required to pass.
- API tests for all of the Servlet API in all related packages:
 - `jakarta.servlet`
 - `jakarta.servlet.annotation`
 - `jakarta.servlet.descriptor`
 - `jakarta.servlet.http`

The Servlet TCK tests run on the following platforms:

- CentOS Linux 7
- Alpine Linux v3.12

1.2.3 JavaTest Harness

The JavaTest harness version 5.0 is a set of tools designed to run and manage test suites on different Java platforms. To JavaTest, Jakarta EE can be considered another platform. The JavaTest harness can be described as both a Java application and a set of compatibility testing tools. It can run tests on different kinds of Java platforms and it allows the results to be browsed online within the JavaTest GUI, or offline in the HTML reports that the JavaTest harness generates.

The JavaTest harness includes the applications and tools that are used for test execution and test suite management. It supports the following features:

- Sequencing of tests, allowing them to be loaded and executed automatically
- Graphic user interface (GUI) for ease of use
- Automated reporting capability to minimize manual errors
- Failure analysis
- Test result auditing and auditable test specification framework
- Distributed testing environment support

To run tests using the JavaTest harness, you specify which tests in the test suite to run, how to run them, and where to put the results as described in [Chapter 4, "Setup and Configuration."](#)

1.2.4 TCK Compatibility Test Suite

The test suite is the collection of tests used by the JavaTest harness to test a particular technology implementation. In this case, it is the collection of tests used by the Servlet TCK 5.0 to test a Servlet 5.0 implementation. The tests are designed to verify that a vendor's runtime implementation of the technology complies with the appropriate specification. The individual tests correspond to assertions of the specification.

The tests that make up the TCK compatibility test suite are precompiled and indexed within the TCK test directory structure. When a test run is started, the JavaTest harness scans through the set of tests that are located under the directories that have been selected. While scanning, the JavaTest harness selects the appropriate tests according to any matches with the filters you are using and queues them up for execution.

1.2.5 Exclude Lists

Each version of a TCK includes an Exclude List contained in a `.jtx` file. This is a list of test file URLs that identify tests which do not have to be run for the specific version of the TCK being used. Whenever tests are run, the JavaTest harness automatically excludes any test on the Exclude List from being executed.

A vendor's compatible implementation is not required to pass or run any test on the Exclude List. The Exclude List file, `<TS_HOME>/bin/ts.jtx`, is included in the Servlet TCK.



From time to time, updates to the Exclude List are made available. The exclude list is included in the Jakarta TCK ZIP archive. Each time an update is approved and released, the version number will be incremented. You should always make sure you are using an up-to-date copy of the Exclude List before running the Servlet TCK to verify your implementation.

A test might be in the Exclude List for reasons such as:

- An error in an underlying implementation API has been discovered which does not allow the test to execute properly.
- An error in the specification that was used as the basis of the test has been discovered.
- An error in the test itself has been discovered.
- The test fails due to a bug in the tools (such as the JavaTest harness, for example).

In addition, all tests are run against the compatible implementations. Any tests that fail when run on a compatible Jakarta platform are put on the Exclude List. Any test that is not specification-based, or for which the specification is vague, may be excluded. Any test that is found to be implementation dependent (based on a particular thread scheduling model, based on a particular file system behavior, and so on) may be excluded.



Vendors are not permitted to alter or modify Exclude Lists. Changes to an Exclude List can only be made by using the procedure described in [Section 2.3.1, "TCK Test Appeals Steps."](#)

1.2.6 TCK Configuration

You need to set several variables in your test environment, modify properties in the `<TS_HOME>/bin/ts.jte` file, and then use the JavaTest harness to configure and run the Servlet tests, as described in [Chapter 4, "Setup and Configuration."](#)



The Jakarta EE Specification Process support multiple compatible implementations. These instructions explain how to get started with the Eclipse GlassFish 6.0 CI. If you are using another compatible implementation, refer to material provided by that implementation for specific instructions and procedures.

1.3 Getting Started With the TCK

This section provides an general overview of what needs to be done to install, set up, test, and use the Servlet TCK. These steps are explained in more detail in subsequent chapters of this guide.

1. Make sure that the following software has been correctly installed on the system hosting the JavaTest harness:
 - A Jakarta EE 9 Compatible Implementation (for example Eclipse GlassFish 6.0) or, at a minimum, a Web server with a Servlet container
 - Java SE 8
 - Apache Ant 1.10.0+
 - A CI for Servlet 5.0. One example is Eclipse GlassFish 6.0.
 - Servlet TCK version 5.0, which includes:
 - JDOM 1.1.3
 - Apache Commons HTTP Client 3.1
 - Apache Commons Logging 1.1.3
 - Apache Commons Codec 1.9
 - The Servlet 5.0 Vendor Implementation (VI)

See the documentation for each of these software applications for installation instructions. See [Chapter 3, "Installation,"](#) for instructions on installing the Servlet TCK.

 1. Set up the Servlet TCK software.

See [Chapter 4, "Setup and Configuration,"](#) for details about the following steps.

 1. Set up your shell environment.
 2. Modify the required properties in the `<TS_HOME>/bin/ts.jte` file.
 3. Configure the JavaTest harness.
 2. Test the Servlet 5.0 implementation.

Test the Servlet implementation installation by running the test suite. See [Chapter 5, "Executing Tests."](#)

2 Procedure for Certification

This chapter describes the compatibility testing procedure and compatibility requirements for Jakarta Servlet. This chapter contains the following sections:

- [Certification Overview](#)
- [Compatibility Requirements](#)
- [Test Appeals Process](#)
- [Specifications for Jakarta Servlet](#)
- [Libraries for Jakarta Servlet](#)

2.1 Certification Overview

The certification process for Servlet 5.0 consists of the following activities:

- Install the appropriate version of the Technology Compatibility Kit (TCK) and execute it in accordance with the instructions in this User's Guide.
- Ensure that you meet the requirements outlined in [Compatibility Requirements](#) below.
- Certify to the Eclipse Foundation that you have finished testing and that you meet all of the compatibility requirements, as required by the Eclipse Foundation TCK License.

2.2 Compatibility Requirements

The compatibility requirements for Servlet 5.0 consist of meeting the requirements set forth by the rules and associated definitions contained in this section.

2.2.1 Definitions

These definitions are for use only with these compatibility requirements and are not intended for any other purpose.

Table 2-1 Definitions

Term	Definition
API Definition Product	A Product for which the only Java class files contained in the product are those corresponding to the application programming interfaces defined by the Specifications, and which is intended only as a means for formally specifying the application programming interfaces defined by the Specifications.
Computational Resource	<p>A piece of hardware or software that may vary in quantity, existence, or version, which may be required to exist in a minimum quantity and/or at a specific or minimum revision level so as to satisfy the requirements of the Test Suite.</p> <p>Examples of computational resources that may vary in quantity are RAM and file descriptors.</p> <p>Examples of computational resources that may vary in existence (that is, may or may not exist) are graphics cards and device drivers.</p> <p>Examples of computational resources that may vary in version are operating systems and device drivers.</p>
Configuration Descriptor	Any file whose format is well defined by a specification and which contains configuration information for a set of Java classes, archive, or other feature defined in the specification.
Conformance Tests	All tests in the Test Suite for an indicated Technology Under Test, as released and distributed by the Eclipse Foundation, excluding those tests on the published Exclude List for the Technology Under Test.
Container	An implementation of the associated Libraries, as specified in the Specifications, and a version of a Java Platform, Standard Edition Runtime Product, as specified in the Specifications, or a later version of a Java Platform, Standard Edition Runtime Product that also meets these compatibility requirements.
Documented	Made technically accessible and made known to users, typically by means such as marketing materials, product documentation, usage messages, or developer support programs.
Exclude List	The most current list of tests, released and distributed by the Eclipse Foundation, that are not required to be passed to certify conformance. The Jakarta EE Specification Committee may add to the Exclude List for that Test Suite as needed at any time, in which case the updated TCK version supplants any previous Exclude Lists for that Test Suite.
Libraries	<p>The class libraries, as specified through the Jakarta EE Specification Process (JESP), for the Technology Under Test.</p> <p>The Libraries for Jakarta Servlet are listed at the end of this chapter.</p>

Term	Definition
Location Resource	<p>A location of classes or native libraries that are components of the test tools or tests, such that these classes or libraries may be required to exist in a certain location in order to satisfy the requirements of the test suite.</p> <p>For example, classes may be required to exist in directories named in a CLASSPATH variable, or native libraries may be required to exist in directories named in a PATH variable.</p>
Maintenance Lead	<p>The corresponding Jakarta EE Specification Project is responsible for maintaining the Specification, and the TCK for the Technology. The Specification Project Team will propose revisions and updates to the Jakarta EE Specification Committee which will approve and release new versions of the specification and TCK.</p>
Operating Mode	<p>Any Documented option of a Product that can be changed by a user in order to modify the behavior of the Product.</p> <p>For example, an Operating Mode can be binary (enable/disable optimization), an enumeration (select from a list of protocols), or a range (set the maximum number of active threads).</p> <p>Note that an Operating Mode may be selected by a command line switch, an environment variable, a GUI user interface element, a configuration or control file, etc.</p>
Product	<p>A vendor's product in which the Technology Under Test is implemented or incorporated, and that is subject to compatibility testing.</p>
Product Configuration	<p>A specific setting or instantiation of an Operating Mode.</p> <p>For example, a Product supporting an Operating Mode that permits user selection of an external encryption package may have a Product Configuration that links the Product to that encryption package.</p>
Rebuildable Tests	<p>Tests that must be built using an implementation-specific mechanism. This mechanism must produce specification-defined artifacts. Rebuilding and running these tests against a known compatible implementation verifies that the mechanism generates compatible artifacts.</p>
Resource	<p>A Computational Resource, a Location Resource, or a Security Resource.</p>
Rules	<p>These definitions and rules in this Compatibility Requirements section of this User's Guide.</p>
Runtime	<p>The Containers specified in the Specifications.</p>

Term	Definition
Security Resource	<p>A security privilege or policy necessary for the proper execution of the Test Suite.</p> <p>For example, the user executing the Test Suite will need the privilege to access the files and network resources necessary for use of the Product.</p>
Specifications	<p>The documents produced through the Jakarta EE Specification Process (JESP) that define a particular Version of a Technology.</p> <p>The Specifications for the Technology Under Test are referenced later in this chapter.</p>
Technology	Specifications and one or more compatible implementations produced through the Jakarta EE Specification Process (JESP).
Technology Under Test	Specifications and a compatible implementation for Jakarta Servlet Version 5.0.
Test Suite	The requirements, tests, and testing tools distributed by the Maintenance Lead as applicable to a given Version of the Technology.
Version	A release of the Technology, as produced through the Jakarta EE Specification Process (JESP).

2.2.2 Rules for Jakarta Servlet Products

The following rules apply for each version of an operating system, software component, and hardware platform Documented as supporting the Product:

Servlet1 The Product must be able to satisfy all applicable compatibility requirements, including passing all Conformance Tests, in every Product Configuration and in every combination of Product Configurations, except only as specifically exempted by these Rules.

For example, if a Product provides distinct Operating Modes to optimize performance, then that Product must satisfy all applicable compatibility requirements for a Product in each Product Configuration, and combination of Product Configurations, of those Operating Modes.

Servlet1.1 If an Operating Mode controls a Resource necessary for the basic execution of the Test Suite, testing may always use a Product Configuration of that Operating Mode providing that Resource, even if other Product Configurations do not provide that Resource. Notwithstanding such exceptions, each Product must have at least one set of Product Configurations of such Operating Modes that is able to pass all the Conformance Tests.

For example, a Product with an Operating Mode that controls a security policy (i.e., Security Resource) which has one or more Product Configurations that cause Conformance Tests to fail may be tested

using a Product Configuration that allows all Conformance Tests to pass.

Servlet1.2 A Product Configuration of an Operating Mode that causes the Product to report only version, usage, or diagnostic information is exempted from these compatibility rules.

Servlet1.3 An API Definition Product is exempt from all functional testing requirements defined here, except the signature tests.

Servlet2 Some Conformance Tests may have properties that may be changed. Properties that can be changed are identified in the configuration interview. Properties that can be changed are identified in the JavaTest Environment (.jte) files in the Test Suite installation. Apart from changing such properties and other allowed modifications described in this User's Guide (if any), no source or binary code for a Conformance Test may be altered in any way without prior written permission. Any such allowed alterations to the Conformance Tests will be provided via the Jakarta EE Specification Project website and apply to all vendor compatible implementations.

Servlet3 The testing tools supplied as part of the Test Suite or as updated by the Maintenance Lead must be used to certify compliance.

Servlet4 The Exclude List associated with the Test Suite cannot be modified.

Servlet5 The Maintenance Lead can define exceptions to these Rules. Such exceptions would be made available as above, and will apply to all vendor implementations.

Servlet6 All hardware and software component additions, deletions, and modifications to a Documented supporting hardware/software platform, that are not part of the Product but required for the Product to satisfy the compatibility requirements, must be Documented and available to users of the Product.

For example, if a patch to a particular version of a supporting operating system is required for the Product to pass the Conformance Tests, that patch must be Documented and available to users of the Product.

Servlet7 The Product must contain the full set of public and protected classes and interfaces for all the Libraries. Those classes and interfaces must contain exactly the set of public and protected methods, constructors, and fields defined by the Specifications for those Libraries. No subsetting, supersetting, or modifications of the public and protected API of the Libraries are allowed except only as specifically exempted by these Rules.

Servlet7.1 If a Product includes Technologies in addition to the Technology Under Test, then it must contain the full set of combined public and protected classes and interfaces. The API of the Product must contain the union of the included Technologies. No further modifications to the APIs of the included Technologies are allowed.

Servlet8 Except for tests specifically required by this TCK to be rebuilt (if any), the binary Conformance Tests supplied as part of the Test Suite or as updated by the Maintenance Lead must be used to certify compliance.

Servlet9 The functional programmatic behavior of any binary class or interface must be that defined by the Specifications.

Servlet10 Each Container must make technically accessible all Java SE Runtime interfaces and functionality, as defined by the Specifications, to programs running in the Container, except only as specifically exempted by these Rules.

Servlet10.1 Containers may impose security constraints, as defined by the Specifications.

2.3 Test Appeals Process

Jakarta has a well established process for managing challenges to its TCKs. Any implementor may submit a challenge to one or more tests in the Servlet TCK as it relates to their implementation. Implementor means the entity as a whole in charge of producing the final certified release. **Challenges filed should represent the consensus of that entity.**

2.3.1 Valid Challenges

Any test case (e.g., test class, @Test method), test case configuration (e.g., deployment descriptor), test beans, annotations, and other resources considered part of the TCK may be challenged.

The following scenarios are considered in scope for test challenges:

- Claims that a test assertion conflicts with the specification.
- Claims that a test asserts requirements over and above that of the specification.
- Claims that an assertion of the specification is not sufficiently implementable.
- Claims that a test is not portable or depends on a particular implementation.

2.3.2 Invalid Challenges

The following scenarios are considered out of scope for test challenges and will be immediately closed if filed:

- Challenging an implementation's claim of passing a test. Certification is an honor system and these issues must be raised directly with the implementation.
- Challenging the usefulness of a specification requirement. The challenge process cannot be used to bypass the specification process and raise in question the need or relevance of a specification requirement.
- Claims the TCK is inadequate or missing assertions required by the specification. See the Improvement section, which is outside the scope of test challenges.
- Challenges that do not represent a consensus of the implementing community will be closed until such time that the community does agree or agreement cannot be made. The test challenge process

is not the place for implementations to initiate their own internal discussions.

- Challenges to tests that are already excluded for any reason.
- Challenges that an excluded test should not have been excluded and should be re-added should be opened as a new enhancement request

Test challenges must be made in writing via the Servlet specification project issue tracker as described in [Section 2.3.3, "TCK Test Appeals Steps."](#)

All tests found to be invalid will be placed on the Exclude List for that version of the Servlet TCK.

2.3.3 TCK Test Appeals Steps

1. Challenges should be filed via the Jakarta Servlet specification project's issue tracker using the label **challenge** and include the following information:
 - The relevant specification version and section number(s)
 - The coordinates of the challenged test(s)
 - The exact TCK and exclude list versions
 - The implementation being tested, including name and company
 - The full test name
 - A full description of why the test is invalid and what the correct behavior is believed to be
 - Any supporting material; debug logs, test output, test logs, run scripts, etc.
2. Specification project evaluates the challenge.
 Challenges can be resolved by a specification project lead, or a project challenge triage team, after a consensus of the specification project committers is reached or attempts to gain consensus fails. Specification projects may exercise lazy consensus, voting or any practice that follows the principles of Eclipse Foundation Development Process. The expected timeframe for a response is two weeks or less. If consensus cannot be reached by the specification project for a prolonged period of time, the default recommendation is to exclude the tests and address the dispute in a future revision of the specification.
3. Accepted Challenges.
 A consensus that a test produces invalid results will result in the exclusion of that test from certification requirements, and an immediate update and release of an official distribution of the TCK including the new exclude list. The associated **challenge** issue must be closed with an **accepted** label to indicate it has been resolved.
4. Rejected Challenges and Remedy.
 When a `challenge`` issue is rejected, it must be closed with a label of **invalid** to indicate it has been rejected. There appeal process for challenges rejected on technical terms is outlined in Escalation Appeal. If, however, an implementer feels the TCK challenge process was not followed, an appeal issue should be filed with specification project's TCK issue tracker using the label **challenge-appeal**.

A project lead should escalate the issue with the Jakarta EE Specification Committee via email (jakarta.ee-spec.committee@eclipse.org). The committee will evaluate the matter purely in terms of due process. If the appeal is accepted, the original TCK challenge issue will be reopened and a label of `appealed-challenge` added, along with a discussion of the appeal decision, and the `challenge-appeal` issue will be closed. If the appeal is rejected, the `challenge-appeal` issue should be closed with a label of `invalid`.

5. Escalation Appeal.

If there is a concern that a TCK process issue has not been resolved satisfactorily, the [Eclipse Development Process Grievance Handling](#) procedure should be followed to escalate the resolution. Note that this is not a mechanism to attempt to handle implementation specific issues.

2.4 Specifications for Jakarta Servlet

The Jakarta Servlet specification is available from the specification project web-site: <https://jakarta.ee/specifications/servlet/5.0/>.

2.5 Libraries for Jakarta Servlet

The following is a list of the packages comprising the required class libraries for Servlet 5.0:

- `jakarta.servlet`
- `jakarta.servlet.annotation`
- `jakarta.servlet.descriptor`
- `jakarta.servlet.http`

For the latest list of packages, also see:

<https://jakarta.ee/specifications/servlet/5.0/>

3 Installation

This chapter explains how to install the Jakarta Servlet TCK software.

After installing the software according to the instructions in this chapter, proceed to [Chapter 4, "Setup and Configuration,"](#) for instructions on configuring your test environment.

3.1 Obtaining a Compatible Implementation

Each compatible implementation (CI) will provide instructions for obtaining their implementation. Eclipse GlassFish 6.0 is a compatible implementation which may be obtained from <https://projects.eclipse.org/projects/ee4j.glassfish>

3.2 Installing the Software

Before you can run the Servlet TCK tests, you must install and set up the following software components:

- A Jakarta EE 9 Compatible Implementation (for example Eclipse GlassFish 6.0) or, at a minimum, a Web server with a Servlet container
- Java SE 8
- Apache Ant 1.10.0+
- A CI for Servlet 5.0, one example is Eclipse GlassFish 6.0
- Servlet TCK version 5.0, which includes:
 - JDOM 1.1.3
 - Apache Commons HTTP Client 3.1
 - Apache Commons Logging 1.1.3
 - Apache Commons Codec 1.9
- The Servlet 5.0 Vendor Implementation (VI)

Follow these steps:

1. Install the Java SE 8 software, if it is not already installed.
Download and install the Java SE 8 software from <http://www.oracle.com/technetwork/java/javase/downloads/index.html>. Refer to the installation instructions that accompany the software for additional information.
2. Install the Apache Ant 1.10.0+ software, if it is not already installed.

Download and install Apache Ant 1.10.0+ software from Apache Ant Project. For complete information about Ant, refer to the extensive documentation on the Apache Ant Project site. The Apache Ant Manual is available at <http://ant.apache.org/manual/index.html>. Apache Ant is protected under the Apache Software, License 2.0, which is available on the Apache Ant Project license page at <http://ant.apache.org/license.html>.

3. Install the Servlet TCK 5.0 software.

1. Copy or download the Servlet TCK software to your local system.

You can obtain the Servlet TCK software from the Jakarta EE site <https://jakarta.ee/specifications/servlet/5.0/>.

2. Use the `unzip` command to extract the bundle in the directory of your choice:

```
unzip jakarta-servlet-tck-5.0.0.zip
```

This creates the TCK directory. The TCK is the test suite home, `<TS_HOME>`.

1. Install the Jakarta EE 9 CI software (the servlet Web container used for running the Servlet TCK with the Servlet 5.0 CI), if it is not already installed.

Download and install the Servlet Web container with the Servlet 5.0 CI used for running the Servlet TCK 5.0, represented by the Jakarta EE 9 CI. If you intend to use Eclipse GlassFish 6.0, you may obtain this software via the downloads tab from the project website: <https://projects.eclipse.org/projects/ee4j.glassfish>.

2. Install a Servlet 5.0 Compatible Implementation.

A Compatible Implementation is used to validate your initial configuration and setup of the Servlet TCK 5.0 tests, which are explained further in [Chapter 4, "Setup and Configuration."](#)

The Compatible Implementations for Servlet are listed on the Jakarta EE Specifications web site: <https://jakarta.ee/specifications/servlet/5.0/>.

1. Install a Web server on which the Servlet TCK test applications can be published for testing the VI.

2. Install the Servlet VI to be tested.

Follow the installation instructions for the particular VI under test.

4 Setup and Configuration



The Jakarta EE Specification process provides for any number of compatible implementations. As additional implementations become available, refer to project or product documentation from those vendors for specific TCK setup and operational guidance.

This chapter describes how to set up the Servlet TCK and JavaTest harness software. Before proceeding with the instructions in this chapter, be sure to install all required software, as described in [Chapter 3, "Installation."](#)

After completing the instructions in this chapter, proceed to [Chapter 5, "Executing Tests,"](#) for instructions on running the Servlet TCK.

4.4 Custom Configuration Handlers

Configuration handlers are used to configure and unconfigure a Servlet 5.0 implementation during the certification process. These are similar to deployment handlers but used for configuration. A configuration handler is an Ant build file that contains at least the required targets listed below:

- `config.vi` - to configure the vendor implementation
- `clean.vi` - to unconfigure the vendor implementation

These targets are called from the `<TS_HOME>/bin/build.xml` file and call down into the implementation-specific configuration handlers.

To provide your own configuration handler, create a `config.vi.xml` file with the necessary configuration steps for your implementation and place the file under the `<TS_HOME>/bin/xml/impl/<your_impl>` directory.

For more information, you may wish to view `<TS_HOME>/bin/xml/impl/glassfish/config.vi.xml`, the configuration file for Jakarta EE 9 Compatible Implementation, Eclipse GlassFish.

4.5 Custom Deployment Handlers

Deployment handlers are used to deploy and undeploy the WAR files that contain the tests to be run during the certification process. A deployment handler is an Ant build file that contains at least the required targets listed in the table below.

The Servlet TCK provides these deployment handlers:

- `<TS_HOME>/bin/xml/impl/none/deploy.xml`
- `<TS_HOME>/bin/xml/impl/glassfish/deploy.xml`
- `<TS_HOME>/bin/xml/impl/tomcat/deploy.xml`

The `deploy.xml` files in each of these directories are used to control deployment to a specific container (no deployment, deployment to the Eclipse GlassFish Web container, deployment to the Tomcat Web container) denoted by the name of the directory in which each `deploy.xml` file resides. The primary `build.xml` file in the `<TS_HOME>/bin` directory has a target to invoke any of the required targets (`-deploy`, `-undeploy`, `-deploy.all`, `-undeploy.all`).

4.5.1 To Create a Custom Deployment Handler

To deploy tests to another Servlet implementation, you must create a custom handler.

1. Create a new directory in the `<TS_HOME>/bin/xml/impl` directory tree. For example, create the `<TS_HOME>/bin/xml/impl/my_deployment_handler` directory. Replace `my_deployment_handler` with the value of the `impl.vi` property that you set in Step 5 of the configuration procedure described in Section 4.2, "Configuring Your Environment to Repackage and Run the TCK Against the Vendor Implementation".
2. Copy the `deploy.xml` file from the `<TS_HOME>/bin/xml/impl/none` directory to the directory that you created.
3. Modify the required targets in the `deploy.xml` file. This is what the `deploy.xml` file for the "none" deployment handler looks like.

```
<project name="No-op Deployment" default="deploy">
  <!-- No-op deployment target -->
  <target name="-deploy">
    <echo message="No deploy target implemented for this deliverable"/>
  </target>
  <target name="-undeploy">
    <echo message="No undeploy target implemented for this deliverable"/>
  </target>
  <target name="-deploy.all">
    <echo message="No deploy target implemented for this deliverable"/>
  </target>
  <target name="-undeploy.all">
    <echo message="No undeploy target implemented for this deliverable"/>
  </target>
</project>
```

Although this example just echoes messages, it does include the four required Ant targets (`-deploy`, `-undeploy`, `-deploy.all`, `-undeploy.all`) that your custom `deploy.xml` file must contain. With this as your starting point, look at the required targets in the `deploy.xml` files in the Tomcat and Eclipse

Glassfish directories for guidance as you create the same targets for the Web container in which you will run your implementation of Servlet.

The following Ant targets can be called from anywhere under the `<TS_HOME>/src` directory:

- `deploy`
- `undeploy`
- `deploy.all`
- `undeploy.all`

The `deploy.all` and `undeploy.all` targets can also be called from the `<TS_HOME>/bin` directory.



The targets in the `deploy.xml` file are never called directly. They are called indirectly by the targets listed above.

4.6 Using the JavaTest Harness Software

There are two general ways to run the Servlet TCK test suite using the JavaTest harness software:

- Through the JavaTest GUI; if using this method, please continue on to [Section 4.7, "Using the JavaTest Harness Configuration GUI."](#)
- In JavaTest batch mode, from the command line in your shell environment; if using this method, please proceed directly to [Chapter 5, "Executing Tests."](#)

4.7 Using the JavaTest Harness Configuration GUI

You can use the JavaTest harness GUI to modify general test settings and to quickly get started with the default Servlet TCK test environment. This section covers the following topics:

- [Configuration GUI Overview](#)
- [Starting the Configuration GUI](#)
- [To Configure the JavaTest Harness to Run the Servlet TCK Tests](#)
- [Modifying the Default Test Configuration](#)



It is only necessary to proceed with this section if you want to run the JavaTest harness in GUI mode. If you plan to run the JavaTest harness in command-line mode, skip the remainder of this chapter, and continue with [Chapter 5, "Executing Tests."](#)

4.7.1 Configuration GUI Overview

In order for the JavaTest harness to execute the test suite, it requires information about how your computing environment is configured. The JavaTest harness requires two types of configuration information:

- **Test environment:** This is data used by the tests. For example, the path to the Java runtime, how to start the product being tested, network resources, and other information required by the tests in order to run. This information does not change frequently and usually stays constant from test run to test run.
- **Test parameters:** This is information used by the JavaTest harness to run the tests. Test parameters are values used by the JavaTest harness that determine which tests in the test suite are run, how the tests should be run, and where the test reports are stored. This information often changes from test run to test run.

The first time you run the JavaTest harness software, you are asked to specify the test suite and work directory that you want to use. (These parameters can be changed later from within the JavaTest harness GUI.)

Once the JavaTest harness GUI is displayed, whenever you choose Start, then Run Tests to begin a test run, the JavaTest harness determines whether all of the required configuration information has been supplied:

- If the test environment and parameters have been completely configured, the test run starts immediately.
- If any required configuration information is missing, the configuration editor displays a series of questions asking you the necessary information. This is called the configuration interview. When you have entered the configuration data, you are asked if you wish to proceed with running the test.

4.7.2 Starting the Configuration GUI

Before you start the JavaTest harness software, you must have a valid test suite and Java SE 8 installed on your system.

The Servlet TCK includes an Ant script that is used to execute the JavaTest harness from the `<TS_HOME>` directory. Using this Ant script to start the JavaTest harness is part of the procedure described in [Section 4.7.3, "To Configure the JavaTest Harness to Run the TCK Tests."](#)

When you execute the JavaTest harness software for the first time, the JavaTest harness displays a Welcome dialog box that guides you through the initial startup configuration.

- If it is able to open a test suite, the JavaTest harness displays a Welcome to JavaTest dialog box that guides you through the process of either opening an existing work directory or creating a new

work directory as described in the JavaTest online help.

- If the JavaTest harness is unable to open a test suite, it displays a Welcome to JavaTest dialog box that guides you through the process of opening both a test suite and a work directory as described in the JavaTest documentation.

After you specify a work directory, you can use the Test Manager to configure and run tests as described in [Section 4.7.3, "To Configure the JavaTest Harness to Run the TCK Tests."](#)

4.7.3 To Configure the JavaTest Harness to Run the TCK Tests

The answers you give to some of the configuration interview questions are specific to your site. For example, the name of the host on which the JavaTest harness is running. Other configuration parameters can be set however you wish. For example, where you want test report files to be stored.

Note that you only need to complete all these steps the first time you start the JavaTest test harness. After you complete these steps, you can either run all of the tests by completing the steps in [Section 5.1, "Starting JavaTest,"](#) or run a subset of the tests by completing the steps in [Section 5.2, "Running a Subset of the Tests."](#)

1. Change to the `<TS_HOME>/bin` directory and start the JavaTest test harness:

```
cd <TS_HOME>/bin
ant gui
```
2. From the File menu, click **Open Quick Start Wizard**.
The Welcome screen displays.
3. Select **Start a new test run**, and then click **Next**.
You are prompted to create a new configuration or use a configuration template.
4. Select **Create a new configuration**, and then click **Next**.
You are prompted to select a test suite.
5. Accept the default suite (`<TS_HOME>/src`), and then click **Next**.
You are prompted to specify a work directory to use to store your test results.
6. Type a work directory name or use the **Browse** button to select a work directory, and then click **Next**.
You are prompted to start the configuration editor or start a test run. At this point, the Servlet TCK is configured to run the default test suite.
7. Deselect the **Start the configuration editor** option, and then click **Finish**.
8. Click **Run Tests**, then click **Start**.
The JavaTest harness starts running the tests.
9. To reconfigure the JavaTest test harness, do one of the following:
 - Click **Configuration**, then click **New Configuration**.

- Click **Configuration**, then click **Change Configuration**.
10. Click **Report**, and then click **Create Report**.
 11. Specify the directory in which the JavaTest test harness will write the report, and then click **OK**.
A report is created, and you are asked whether you want to view it.
 12. Click **Yes** to view the report.

4.7.4 Modifying the Default Test Configuration

The JavaTest GUI enables you to configure numerous test options. These options are divided into two general dialog box groups:

- Group 1: Available from the JavaTest **Configure/Change Configuration** submenus, the following options are displayed in a tabbed dialog box:
 - **Tests to Run**
 - **Exclude List**
 - **Keywords**
 - **Prior Status**
 - **Test Environment**
 - **Concurrency**
 - **Timeout Factor**
- Group 2: Available from the JavaTest **Configure/Change Configuration/Other Values** submenu, or by pressing **Ctrl+E**, the following options are displayed in a paged dialog box:
 - **Environment Files**
 - **Test Environment**
 - **Specify Tests to Run**
 - **Specify an Exclude List**

Note that there is some overlap between the functions in these two dialog boxes; for those functions use the dialog box that is most convenient for you. Please refer to the JavaTest Harness documentation or the online help for complete information about these various options.

5 Executing Tests

The Servlet TCK uses the JavaTest harness to execute the tests in the test suite. For detailed instructions that explain how to run and use JavaTest, see the JavaTest User's Guide and Reference in the documentation bundle.

This chapter includes the following topics:

- [Starting JavaTest](#)
- [Running a Subset of the Tests](#)
- [Running the TCK Against your selected CI](#)
- [Running the TCK Against a Vendor's Implementation](#)
- [Test Reports](#)



The instructions in this chapter assume that you have installed and configured your test environment as described in [Chapter 3, "Installation,"](#) and [Chapter 4, "Setup and Configuration,"](#) respectively.

As explained in [Appendix B, "Packaging the Test Applications in Servlet-Compliant WAR Files With VI-Specific Information,"](#) the Servlet TCK introduces the concept of repackaging the TCK tests.

5.1 Starting JavaTest

There are two general ways to run the Servlet TCK using the JavaTest harness software:

- Through the JavaTest GUI
- From the command line in your shell environment



The `ant` command referenced in the following two procedures and elsewhere in this guide is the Apache Ant build tool, which will need to be downloaded separately. The `build.xml` file in `<TS_HOME>/bin` contains the various Ant targets for the Servlet TCK test suite.

5.1.1 To Start JavaTest in GUI Mode

Execute the following commands:

```
cd <TS_HOME>/bin
ant gui
```

5.1.2 To Start JavaTest in Command-Line Mode

1. Change to any subdirectory under `<TS_HOME>/src/com/sun/ts/tests`.
2. Start JavaTest using the following command:

```
ant runclient
```

Example 5-1 Servlet TCK Signature Tests

To run the Servlet TCK signature tests, enter the following commands:

```
cd <TS_HOME>/src/com/sun/ts/tests/signaturetest/servlet
ant runclient
```

Example 5-2 Single Test Directory

To run a single test directory, enter the following commands:

```
cd <TS_HOME>/src/com/sun/ts/tests/servlet/api/client
ant runclient
```

Example 5-3 Subset of Test Directories

To run a subset of test directories, enter the following commands:

```
cd <TS_HOME>/src/com/sun/ts/tests/servlet/api
ant runclient
```

5.2 Running a Subset of the Tests

Use the following modes to run a subset of the tests:

- [Section 5.2.1, "To Run a Subset of Tests in GUI Mode"](#)

- [Section 5.2.2, "To Run a Subset of Tests in Command-Line Mode"](#)
- [Section 5.2.3, "To Run a Subset of Tests in Batch Mode Based on Prior Result Status"](#)

5.2.1 To Run a Subset of Tests in GUI Mode

1. From the JavaTest main menu, click **Configure**, then click **Change Configuration**, and then click **Tests to Run**.
The tabbed Configuration Editor dialog box is displayed.
2. Click **Specify** from the option list on the left.
3. Select the tests you want to run from the displayed test tree, and then click **Done**.
You can select entire branches of the test tree, or use **Ctrl+Click** or **Shift+Click** to select multiple tests or ranges of tests, respectively, or select just a single test.
4. Click **Save File**.
5. Click **Run Tests**, and then click **Start** to run the tests you selected.
Alternatively, you can **right-click** the test you want from the test tree in the left section of the JavaTest main window, and choose **Execute These Tests** from the menu.
6. Click **Report**, and then click **Create Report**.
7. Specify the directory in which the JavaTest test harness will write the report, and then click **OK**.
A report is created, and you are asked whether you want to view it.
8. Click **Yes** to view the report.

5.2.2 To Run a Subset of Tests in Command-Line Mode

1. Change to the directory containing the tests you want to run.
2. Start the test run by executing the following command:

```
ant runclient
```

The tests in the directory and its subdirectories are run.

5.2.3 To Run a Subset of Tests in Batch Mode Based on Prior Result Status

You can run certain tests in batch mode based on the test's prior run status by specifying the **priorStatus** system property when invoking **ant**

Invoke `ant` with the `priorStatus` property.

The accepted values for the `priorStatus` property are any combination of the following:

- `fail`
- `pass`
- `error`
- `notRun`

For example, you could run all the Servlet tests with a status of failed and error by invoking the following commands:

```
ant -DpriorStatus="fail,error" runclient
```

Note that multiple `priorStatus` values must be separated by commas.

5.3 Running the TCK Against another CI

Some test scenarios are designed to ensure that the configuration and deployment of all the prebuilt Servlet TCK tests against one Compatible Implementation are successful operating with other compatible implementations, and that the TCK is ready for compatibility testing against the Vendor and Compatible Implementations.

1. Verify that you have followed the configuration instructions in [Section 4.1, "Configuring Your Environment to Run the TCK Against the Compatible Implementation."](#)
2. If required, verify that you have completed the steps in [Section 4.3.2, "Deploying the Prebuilt Archives."](#)
3. Run the tests, as described in [Section 5.1, "Starting JavaTest,"](#) and, if desired, [Section 5.2, "Running a Subset of the Tests."](#)

5.4 Running the TCK Against a Vendor's Implementation

This test scenario is one of the compatibility test phases that all Vendors must pass.

1. Verify that you have followed the configuration instructions in [Section 4.2, "Configuring Your Environment to Repackage and Run the TCK Against the Vendor Implementation."](#)
2. If required, verify that you have completed the steps in [Section 4.3.3, "Deploying the Test Applications Against the Vendor Implementation."](#)
3. Run the tests, as described in [Section 5.1, "Starting JavaTest,"](#) and, if desired, [Section 5.2, "Running a](#)

[Subset of the Tests."](#)

5.5 Test Reports

A set of report files is created for every test run. These report files can be found in the report directory you specify. After a test run is completed, the JavaTest harness writes HTML reports for the test run. You can view these files in the JavaTest ReportBrowser when running in GUI mode, or in the web browser of your choice outside the JavaTest interface.

To see all of the HTML report files, enter the URL of the `report.html` file. This file is the root file that links to all of the other HTML reports.

The JavaTest harness also creates a `summary.txt` file in the report directory that you can open in any text editor. The `summary.txt` file contains a list of all tests that were run, their test results, and their status messages.

5.5.1 Creating Test Reports

Use the following modes to create test reports:

- [Section 5.5.1.1, "To Create a Test Report in GUI Mode"](#)
- [Section 5.5.1.2, "To Create a Test Report in Command-Line Mode"](#)

5.5.1.1 To Create a Test Report in GUI Mode

1. From the JavaTest main menu, click **Report**, then click **Create Report**.
You are prompted to specify a directory to use for your test reports.
2. Specify the directory you want to use for your reports, and then click **OK**.
Use the Filter list to specify whether you want to generate reports for the current configuration, all tests, or a custom set of tests.
You are asked whether you want to view report now.
3. Click **Yes** to display the new report in the JavaTest ReportBrowser.

5.5.1.2 To Create a Test Report in Command-Line Mode

1. Specify where you want to create the test report.
 1. To specify the report directory from the command line at runtime, use:

```
ant -Dreport.dir="report_dir"
```

Reports are written for the last test run to the directory you specify.

2. To specify the default report directory, set the `report.dir` property in `<TS_HOME>/bin/ts.jte`.
For example:

```
report.dir="/home/josephine/reports"
```

3. To disable reporting, set the `report.dir` property to `"none"`, either on the command line or in `<TS_HOME>/bin/ts.jte`.
For example:

```
ant -Dreport.dir="none"
```

5.5.2 Viewing an Existing Test Report

Use the following modes to view an existing test report:

- [Section 5.5.2.1, "To View an Existing Report in GUI Mode"](#)
- [Section 5.5.2.2, "To View an Existing Report in Command-Line Mode"](#)

5.5.2.1 To View an Existing Report in GUI Mode

1. From the JavaTest main menu, click **Report**, then click **Open Report**.
You are prompted to specify the directory containing the report you want to open.
2. Select the report directory you want to open, and then click **Open**.
The selected report set is opened in the JavaTest ReportBrowser.

5.5.2.2 To View an Existing Report in Command-Line Mode

Use the Web browser of your choice to view the `report.html` file in the report directory you specified from the command line or in `<TS_HOME>/bin/ts.jte`.

6 Debugging Test Problems

There are a number of reasons that tests can fail to execute properly. This chapter provides some approaches for dealing with these failures. Please note that most of these suggestions are only relevant when running the test harness in GUI mode.

This chapter includes the following topics:

- [Overview](#)
- [Test Tree](#)
- [Folder Information](#)
- [Test Information](#)
- [Report Files](#)
- [Configuration Failures](#)

6.1 Overview

The goal of a test run is for all tests in the test suite that are not filtered out to have passing results. If the root test suite folder contains tests with errors or failing results, you must troubleshoot and correct the cause to satisfactorily complete the test run.

- **Errors:** Tests with errors could not be executed by the JavaTest harness. These errors usually occur because the test environment is not properly configured.
- **Failures:** Tests that fail were executed but had failing results.

The Test Manager GUI provides you with a number of tools for effectively troubleshooting a test run. See the JavaTest User's Guide and JavaTest online help for detailed descriptions of the tools described in this chapter. Ant test execution tasks provide command-line users with immediate test execution feedback to the display. Available JTR report files and log files can also help command-line users troubleshoot test run problems.

For every test run, the JavaTest harness creates a set of report files in the reports directory, which you specified by setting the `report.dir` property in the `<TS_HOME>/bin/ts.jte` file. The report files contain information about the test description, environment, messages, properties used by the test, status of the test, and test result. After a test run is completed, the JavaTest harness writes HTML reports for the test run. You can view these files in the JavaTest ReportBrowser when running in GUI mode, or in the Web browser of your choice outside the JavaTest interface. To see all of the HTML report files, enter the URL of the `report.html` file. This file is the root file that links to all of the other HTML reports.

The JavaTest harness also creates a `summary.txt` file in the report directory that you can open in any text editor. The `summary.txt` file contains a list of all tests that were run, their test results, and their

status messages.

The work directory, which you specified by setting the `work.dir` property in the `<TS_HOME>/bin/ts.jte` file, contains several files that were deposited there during test execution: `harness.trace`, `log.txt`, `lastRun.txt`, and `testsuite`. Most of these files provide information about the harness and environment in which the tests were executed.



You can set `harness.log.traceflag=true` in `<TS_HOME>/bin/ts.jte` to get more debugging information.

If a large number of tests failed, you should read [Configuration Failures](#) to see if a configuration issue is the cause of the failures.

6.2 Test Tree

Use the test tree in the JavaTest GUI to identify specific folders and tests that had errors or failing results. Color codes are used to indicate status as follows:

- Green: Passed
- Blue: Test Error
- Red: Failed to pass test
- White: Test not run
- Gray: Test filtered out (not run)

6.3 Folder Information

Click a folder in the test tree in the JavaTest GUI to display its tabs.

Choose the Error and the Failed tabs to view the lists of all tests in and under a folder that were not successfully run. You can double-click a test in the lists to view its test information.

6.4 Test Information

To display information about a test in the JavaTest GUI, click its icon in the test tree or double-click its name in a folder status tab. The tab contains detailed information about the test run and, at the bottom of the window, a brief status message identifying the type of failure or error. This message may be sufficient for you to identify the cause of the error or failure.

If you need more information to identify the cause of the error or failure, use the following tabs listed in order of importance:

- Test Run Messages contains a Message list and a Message section that display the messages produced during the test run.
- Test Run Details contains a two-column table of name/value pairs recorded when the test was run.
- Configuration contains a two-column table of the test environment name/value pairs derived from the configuration data actually used to run the test.



You can set `harness.log.traceflag=true` in `<TS_HOME>/bin/ts.jte` to get more debugging information.

6.5 Report Files

Report files are another good source of troubleshooting information. You may view the individual results of a batch run in the JavaTest Summary window, but there are also a wide range of HTML report files that you can view in the JavaTest ReportBrowser or in the external browser or your choice following a test run. See [Section 5.5, "Test Reports,"](#) for more information.

6.6 Configuration Failures

Configuration failures are easily recognized because many tests fail the same way. When all your tests begin to fail, you may want to stop the run immediately and start viewing individual test output. However, in the case of full-scale launching problems where no tests are actually processed, report files are usually not created (though sometimes a small `harness.trace` file in the report directory is written).

6.7 Troubleshooting Tips

This section provides some tips for troubleshooting errors that may be encountered.

- Verify that the Ant `config.vi` and `enable.jacc` configuration targets executed correctly.
- If there are several failures during a test run, check the various output for hints about what caused the failures. A common problem is the absence of the Servlet log file. This log file should be created in the directory defined by the `log.file.location` property in the `ts.jte` file. There should be a log file called `JACCLog.txt` in this directory. The `JACCLog.txt` consists of record entries containing permission information that will be used to verify the TCK tests for proper compliance. This log file

typically gets populated with Servlet-based security information when test archives are deployed. Then, during test execution, the `JACCLog.txt` file is read and used for validating that Servlet behavior is correct.

- Simultaneously deploying all Servlet TCK test archives may cause false failures. If unexpected failures occur during a TCK run when all Servlet archives were deployed, these failures could be caused by interference from tests and archives that are defined multiple times. If such situational failures do occur, undeploy all archives, remove the `JACCLog.txt` file, recycle your server (if necessary), and rerun only the tests in the directory that showed failures.
- Check that the following JVM variables, which should have been set by invoking the `enable.jacc` Ant target, have been set in the application server :
 - `-Dlog.file.location` (this comes from the `<TS_HOME>/bin/ts.jte` property)
 - `-Djakarta.security.jacc.policy.provider=com.sun.ts.tests.jacc.provider.TSPolicy`
 - `-Djakarta.security.jacc.PolicyConfigurationFactory.provider=com.sun.ts.tests.jacc.provider.TSPolicyConfigurationFactoryImpl`
 - `-Dvendor.jakarta.security.jacc.policy.provider=com.sun.enterprise.security.provider.PolicyWrapper`
 - `-Dvendor.jakarta.security.jacc.PolicyConfigurationFactory.provider=com.sun.enterprise.security.provider.PolicyConfigurationFactoryImpl`



The values for the `-Dvendor.jakarta.security.jacc.policy.provider` and `-Dvendor.jakarta.security.jacc.PolicyConfigurationFactory.provider` JVM variables will need to be set specific to the application server in use.

A Frequently Asked Questions

This appendix contains the following questions.

- [Where do I start to debug a test failure?](#)
- [How do I restart a crashed test run?](#)
- [What would cause tests be added to the exclude list?](#)

A.1 Where do I start to debug a test failure?

From the JavaTest GUI, you can view recently run tests using the Test Results Summary, by selecting the red Failed tab or the blue Error tab. See [Chapter 6, "Debugging Test Problems,"](#) for more information.

A.2 How do I restart a crashed test run?

If you need to restart a test run, you can figure out which test crashed the test suite by looking at the `harness.trace` file. The `harness.trace` file is in the report directory that you supplied to the JavaTest GUI or parameter file. Examine this trace file, then change the JavaTest GUI initial files to that location or to a directory location below that file, and restart. This will overwrite only `.jtr` files that you rerun. As long as you do not change the value of the GUI work directory, you can continue testing and then later compile a complete report to include results from all such partial runs.

A.3 What would cause tests be added to the exclude list?

The JavaTest exclude file (`<TS_HOME>/bin/ts.jtx`) contains all tests that are not required to be run. The following is a list of reasons for a test to be included in the Exclude List:

- An error in a Compatible Implementation that does not allow the test to execute properly has been discovered.
- An error in the specification that was used as the basis of the test has been discovered.
- An error in the test has been discovered.

B Packaging the Test Applications in Servlet-Compliant WAR Files With VI-Specific Information

The Servlet 5.0 specification specifies how Servlet applications are to be published in a Java SE environment, Jakarta XML Web Services endpoint, or Servlet-compliant Web container.

Servlet TCK test application classes that are to be published in a Java SE environment are located under `$TS_HOME/classes`.

The Servlet TCK comes with prebuilt test WAR files for deployment on Jakarta EE 9 CI Eclipse GlassFish 6.0, which provides a Servlet-compliant Web container. The WAR files are Eclipse GlassFish 6.0-specific, with Eclipse GlassFish 6.0's servlet class and Eclipse GlassFish 6.0's servlet defined in the `web.xml` deployment descriptor. To run the TCK tests against the VI in a Servlet-compliant Web container, the tests need to be repackaged to include the VI-specific servlet, and the VI-specific servlet must be defined in the deployment descriptor.

The Servlet TCK makes it easier for the vendor by including template WAR files that contain all of the necessary files except for the VI-specific servlet adaptor class. The Servlet TCK provides a tool to help with the repackaging task.

This appendix contains the following sections:

- [Overview](#)
- [Creating the VI-Specific Servlet-Compliant WAR Files](#)

B.1 Overview

The set of prebuilt archives and classes that ship with the Servlet TCK were built using the Eclipse GlassFish 6.0 Jakarta EE Compatible Implementation, and must be deployed on a Jakarta EE 9 CI and run against the Eclipse GlassFish 6.0 CI.

The prebuilt Eclipse GlassFish 6.0-specific Servlet-compliant WAR files are located under `$TS_HOME/dist`, and have the keyword `jersey` as part of their name; for example:

```
$TS_HOME/dist/com/sun/ts/tests/jaxrs/ee/rs/get/jaxrs_rs_get_web.war.jersey
```

The names are made unique by including `jersey` to minimize the chances that the files will be overwritten or modified.

The Vendor must create VI-specific Servlet-compliant WAR files if the Vendor chooses to publish on a Servlet-compliant Web container, so that the VI-specific Servlet class will be included instead of the Eclipse GlassFish 6.0-specific Servlet class.

B.2 Creating the TCK VI-Specific Servlet-Compliant WAR Files

All resource and application class files are already compiled. The Vendor needs to package these files. All tests also come with a `web.xml.template` file to be used for generating deployment descriptor files with a VI-specific Servlet definition.

Each test that has a Servlet resource class to publish comes with a template deployment descriptor file. For example, the file `$TS_HOME/src/com/sun/ts/tests/jaxrs/ee/rs/get/web.xml.template` contains the following elements:

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app version="2.5" xmlns="http://java.sun.com/xml/ns/javaee" \
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" \
xsi:schemaLocation="http://java.sun.com/xml/ns/javaee \
http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">
  <servlet>
    <servlet-name>CTSJAX-RSGET</servlet-name>
    <servlet-class>servlet_adaptor</servlet-class>
    <init-param>
      <param-name>jakarta.ws.rs.Application</param-name>
      <param-value>com.sun.ts.tests.jaxrs.ee.rs.get.TSAppConfig</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
  </servlet>
  <servlet-mapping>
    <servlet-name>CTSJAX-RSGET</servlet-name>
    <url-pattern>/*</url-pattern>
  </servlet-mapping>
  <session-config>
    <session-timeout>30</session-timeout>
  </session-config>
</web-app>
```

In this example, the `<servlet-class>` element has a value of `servlet_adaptor`, which is a placeholder for the implementation-specific Servlet class. A Eclipse GlassFish 6.0-specific deployment descriptor also comes with the Servlet TCK, and has the values for the `com.sun.jersey.spi.container.servlet.ServletContainer`:

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app version="2.5" xmlns="http://java.sun.com/xml/ns/javaee" \
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" \
xsi:schemaLocation="http://java.sun.com/xml/ns/javaee \
http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">
  <servlet>
    <servlet-name>CTSJAX-RSGET</servlet-name>
    <servlet-class>
      org.glassfish/jersey/servlet/ServletContainer
    </servlet-class>
    <init-param>
      <param-name>jakarta.ws.rs.Application</param-name>
      <param-value>com.sun.ts.tests.jaxrs.ee.rs.get.TSAppConfig</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
  </servlet>
  <servlet-mapping>
    <servlet-name>CTSJAX-RSGET</servlet-name>
    <url-pattern>/*</url-pattern>
  </servlet-mapping>
  <session-config>
    <session-timeout>30</session-timeout>
  </session-config>
</web-app>
```

The Servlet TCK provides a tool, `${ts.home}/bin/xml/impl/glassfish/jersey.xml`, for the Jakarta EE 5.0 CI that you can use as a model to help you create your own VI-specific Web test application.

B.2.1 To Create a VI-Specific Deployment Descriptor

1. Create a VI handler file.

Create a VI-specific handler file `${TS_HOME}/bin/xml/impl/${impl.vi}/jaxrs_impl_name.xml` if one does not already exist. Make sure the `jaxrs_impl_name` property is set in the `<TS_HOME>/bin/ts.jte` file and that it has a unique name so no file will be overwritten.

2. Set the VI Servlet class property.

Set the `servlet_adaptor` property in the `<TS_HOME>/bin/ts.jte` file. This property will be used to set the value of the `<servlet-class>` element in the deployment descriptor.

3. Create VI Ant tasks.

Create a `update.jaxrs.wars` target in the VI handler file. Reference this `update.jaxrs.wars` target in the `jersey.xml` file.

This target will create a `web.xml.${jaxrs_impl_name}` for each test that has a deployment descriptor template. The `web.xml.${jaxrs_impl_name}` will contain the VI-specific Servlet class

name. It will also create the test WAR files under `$TS_HOME/dist`; for example:

```
ls $TS_HOME/dist/com/sun/ts/tests/jaxrs/ee/rs/get/  
jaxrs_rs_get_web.war.jersey  
jaxrs_rs_get_web.war.${impl_name}
```

4. Change to the `$TS_HOME/bin` directory and execute the `update.jaxrs.wars` Ant target. This creates a ``web.xml.`VI_name` file for each test based on the VI's servlet class name and repackages the tests.