

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

Installation Guide for the TITAN Designer and TITAN Executor for the Eclipse IDE



Abstract

This document describes the detailed information of installing the TITAN Designer and Executor for the Eclipse IDE.

Copyright

Copyright (c) 2000-2016 Ericsson Telecom AB.
All rights reserved. This program and the accompanying materials
are made available under the terms of the Eclipse Public License v1.0
which accompanies this distribution, and is available at

<http://www.eclipse.org/legal/epl-v10.html>.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

Contents

1	Introduction	3
1.1	Overview	3
1.2	Target Groups	3
1.3	Typographical Conventions	3
2	Requirements	4
2.1	Requirements for the TITAN Designer, Executor and Log Viewer plug-ins for the Eclipse IDE	4
2.2	Requirements for the Titanium Plugin	4
2.3	Cygwin on Windows	4
3	Installing prerequisites	5
3.1	Installing the TITAN TTCN-3 Toolset	5
3.2	Installing Eclipse	5
3.3	Installing Eclipse plug-in prerequisites for Titan Plug-ins and Titanium	6
4	Installation of the TITAN plug-ins	6
5	Post-Installation Steps	9
5.1	Turning-Off Automatic Building	10
5.2	Configuring Java	10
6	Compatibility Issues	12
7	References	13

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

1 Introduction

1.1 Overview

This document describes the installation and configuration of the TITAN Designer, the TITAN Executor, the TITAN Log Viewer and the Titanium plug-ins for the Eclipse IDE (from now shortly TITAN plug-ins).

1.2 Target Groups

This document is intended for system administrators and users who intend to install and configure the TITAN Designer, Executor, Log Viewer and Titanium plug-ins for the Eclipse IDE.

1.3 Typographical Conventions

This document uses the following typographical conventions:

- **Bold** is used to represent graphical user interface (GUI) components such as buttons, menus, menu items, dialog box options, fields and keywords, as well as menu commands. Bold is also used with '+' to represent key combinations. For example, **Ctrl+Click**
- The '/' character is used to denote a menu and sub-menu sequence. For example, **File / Open**.
- `Monospaced` font is used represent system elements such as command and parameter names, program names, path names, URLs, directory names and code examples.
- **Bold monospaced font** is used for commands that must be entered at the Command Line Interface (CLI), For example, **mctr_gui**

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

2 Requirements

2.1 Requirements for the TITAN Designer, Executor and Log Viewer plugins for the Eclipse IDE

- Eclipse 3.5 or later (max. 4.6.1 Neon - this one being recommended) and all of its dependencies, for example, GTK2, must be installed
- ANTLR Runtime 4.3
- TITAN TTCN-3 Toolset installed. (Only needed if Eclipse is used for project compilation and test execution. Editing does not require it.)
- J2SE(TM) Runtime Environment 6.0 or later installed and set in Eclipse as the Java Runtime Environment
- Only Oracle Java Hotspot virtual machine is supported

2.2 Requirements for the Titanium Plugin

- TITAN Designer
- JUNG (Java Universal Network/Graph Framework)
Product No.: 2/CAX 105 4836, preferred version: R1A,
see <http://jung.sourceforge.net/>
- Commons-Collections with Generics
Product No.: 1/CAX 105 6260, preferred version: R1A
see <http://commons.apache.org/proper/commons-collections/>
- Apache POI 3.9.0
- ANTLR Runtime 4.3.0

2.3 Cygwin on Windows

Using the Eclipse IDE on Windows is fully supported.

Installing Cygwin is optional and only needed if Eclipse is used for project compilation and test execution. TTCN-3 module editing is supported without Cygwin.

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

For detailed information on installing Cygwin and configuring the environment variables for TITAN to work, refer to Installation Guide for TITAN TTCN-3 Test Executor 1/1531-CRL 113 200/5 Uen.

Only one detail of that document is emphasized here:

'When installation is finished, add the `$CYGWIN_INSTALL_DIRECTORY\bin` directory to the Path environment variable of Windows, so Eclipse will access the shell commands.

For example if the cygwin root is "C:\cygwin64" then "Path" should contain "C:\cygwin64\bin".'

3 Installing prerequisites

3.1 Installing the TITAN TTCN-3 Toolset

For detailed information on installing the TITAN TTCN-3 Toolset, and configuring the environment variables for TITAN to work, refer to Installation Guide for TITAN TTCN-3 Test Executor 1/1531-CRL 113 200/6 Uen.

3.2 Installing Eclipse

Download the latest 32- or 64-bit Eclipse package, according to your platform and OS version from <https://www.eclipse.org/downloads/>.

All Eclipse solution packages are suitable, but if you want to develop also adapters and/or external **C/C++** functions, the "Eclipse IDE for C/C++ Developers" can be a good choice.

Note: The CDT package can also be added to any Eclipse installation later.

If you want to use/edit XML, XSD and/or JSON files, the Eclipse ecosystem provides tools for this.

For **XML/XSD** editing and validation you can use the Web Tool Platform (WTP) project's XML Editor; it is contained in Eclipse IDE for Java EE Developers by default, and in other Eclipse packages it can be added from the project's update site (for other Eclipse releases just replace "luna" with the name of your Eclipse release:

<http://download.eclipse.org/webtools/repository/luna/>

To validate your XSD or XML file(s), select the file(s), right-click on the selection and choose "Validate" from the pop-up menu. You can also validate your document by right clicking in the editor window and selecting "validate" from the pop-up menu.


To work with **JSON**, you can find a JSON editor at the Eclipse Marketplace (Help/Marketplace menu): type in the search field "JSON" and follow the instructions.

Prepared (Subject resp) ETHBAAT Jenő Balasko		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

Decompress the downloaded file in a desired location, then run Eclipse with the executable, `eclipse.exe` or `./eclipse`, for Windows or UNIX, respectively.

Notes for users behind a firewall:

When using Eclipse from behind a firewall, the HTTP proxy must be set, and internal Ericsson locations, for example the update site, must be added to proxy exceptions. An example of the proxy settings in Eclipse:



3.3 Installing Eclipse plug-in prerequisites for Titan Plug-ins and Titanium

The prerequisites for Titan plugins are POI and ANTLR Runtime.

The prerequisites for Titanium Plugin are JUNG and Common Collections with Generics.

These can be installed together with the Titan plug-ins as external dependencies, see the next chapter.

4 Installation of the TITAN plug-ins

1 The TITAN plug-ins for Eclipse can be installed from the provided update sites.

- For Ericsson users only: http://ttcn.ericsson.se/download/update_site.

Prepared (Subject resp) ETHBAAT Jenő Balasko		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

- For users outside Ericsson: <https://projects.eclipse.org/projects/tools.titan/downloads>, Choose the appropriate zip or tgz file, download it and pass the link of the downloaded zip to your Eclipse (like when installing a plugin from an archived update site) or unzip it and pass the link of the folder as update site.


Note: the all_in_one (or the Eclipse plug-ins plus dependencies) package contains ANTLR Runtime, JUNG and common collection, the other packages do not contain any prerequisites.

From version 6.1.0 only all_in_one packages are delivered.


WARNING: If you have an earlier version than 4.2.0.CRL_113_200_4_R2A_20140902-1911 of TITAN plug-ins then any new installation should be preceded by uninstalling of the TITAN plug-ins or to start with a just installed Eclipse from scratch.

Perform the following steps:

- In Eclipse, open the **Help** scroll-down menu, and select the option “**Install New Software...**”.
- Give the provided update site URL in the field or press the button “**Add**”. Fill the Name and location. If a downloaded, zipped update site file is used press the button “**Archive...**” and select the zip file.




The result is something like this:




- Press **OK**. An install dialog appears.

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference




- 5 It is advised to uncheck the “Contact all update sites...” box. Select the TITAN plug-ins and the external dependency plugins to be installed.



Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

- 6 Click **Next**. An Install Details dialog box appears with the items to be installed.
- 7 Click **Next** again.
- 8 Accept the license agreements then push **OK**.
- 9 At this point “Security Warning” window appears indicating that the authenticity or validity of the plug-ins cannot be established.
It is safe to press the **OK** button here.



Note: When you update your TITAN plug-ins, it is suggested to update all the installed TITAN plug-ins because of dependencies. Otherwise eclipse will analyze the dependencies and after a while it will force you to update all of the already installed features.


5 Post-Installation Steps

After installing the TITAN plug-ins in Eclipse, the locations of the installed TITAN TTCN-3 Toolset and the license file must be set.

Open the **Window** scroll-down menu, and open **Preferences**. In the pop-up window, open **TITAN Preferences** from the tree, and set the location of the TITAN installation path and License file (if label “License file” and text box exist in your version).

Note: TITAN install path is not mandatory. If you don’t want to build from Eclipse you can leave it empty.

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference



5.1 Turning-Off Automatic Building

By default, a new installation of Eclipse will be set to automatically compile its projects. In the current build system this can take a lot of time, so it is advised to turn this feature off, and only enabling if the actual projects make it possible. Open the **Project** scroll-down menu, and uncheck the **Build automatically** option.

5.2 Configuring Java

You might need to modify your `eclipse.ini` file (usually located in the same directory as your `eclipse` executable.)

It is suggested to have at least 1GB and recommended 2 GB free memory per 1 million TTCN-3/ASN.1 source code lines (but it strongly depends on the code complexity). In Java it is controlled via the `Xmx` option.

For example, if Java 1.6 or 1.7 is applied and a project of 2 million TTCN-3 code lines is edited, the suggested settings in `eclipse.ini` are these:

```
-vmargs
-XX:MaxPermSize=2048M
-Dosgi.requiredJavaVersion=1.7
-Xms1024M
```

Prepared (Subject resp) ETHBAAT Jeno Balasko		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

-Xmx4g

If Java 1.8 is used then `MaxPermSize` is ignored, its support is removed. Use these settings instead:

```
-vmargs  
-Dosgi.requiredJavaVersion=1.8  
-XX:+UseG1GC  
-Xms1024M  
-Xmx4g
```

Notes:

If you cannot edit the `eclipse.ini` file, you can start eclipse with flags. For example
`eclipse -vmargs -Xmx4g`

modifies the maximum memory allocation for the virtual machine.

Prepared (Subject resp) ETHBAAT Jenő Balaskó		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

6 Compatibility Issues

The plug-ins require the Java Runtime Environment to be version 5.0 or later, but significant speed increase can be gained by installing version 6.0, 7.0 or 8.0.

Note that an actual version of the TITAN Designer plug-in is meant to be compatible with the same version of TITAN, but can be used with older TITAN releases, if:

- The additional features are not used (the makefile generator of TITAN is used to generate the makefile, so if a feature is used that is known by TITAN Designer, but is not known by the makefile generator, the makefile generation will fail)
- A special script is inserted into the actually used install directory's bin directory. The role of this script is to convert the call to the makefile generator to valid call of the compiler. (The makefile generator and the compiler are separated from TITAN 1.7.0). It is important to note, that such a file must contain a path to the compiler to be called, so such a script is not expected to work without modifications. Please note that the compiler must be called with **-m** as the first parameter, and the other parameters must be redirected to the compiler.

Prepared (Subject resp) ETHBAAT Jeno Balasko		No. 3/1531-CRL 113 200/6 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-11-08	Rev A	Reference

7 References

- [1] Installation Guide for TITAN TTCN-3 Test Executor
1/1531-CRL 113 200/6 Uen
- [2] User Guide for TITAN TTCN-3 Test Executor
1/198 17-CRL 113 200/6 Uen
- [3] User Guide for TITAN Designer for the Eclipse IDE
4/198 17-CRL 113 200/6 Uen
- [4] User Guide for TITAN Executor for the Eclipse IDE
5/198 17-CRL 113 200/6 Uen
- [5] Programmer's Technical Reference for TITAN TTCN-3 Test Executor
2/198 17-CRL 113 200/6 Uen